ENERGY WISE FOR YOUR HOME

Your guide to heating and cooling

AIR SOURCE HEAT PUMP (ASHP)

- It's the best of both worlds. ASHPs provide home cooling and supplemental heating with 72% less electricity than conventional air conditioners and furnaces.
- ASHPs are measured by:
 - Heat Seasonal Performance Factor (HSPF). HSPF/ HSPF2 is the most commonly used measure of a heat pumps heating efficiency. The higher the HSPF/ HSPF2, the more efficient the heat pump.
 - 2) Seasonal Energy Efficiency Ratio (SEER). The SEER/ SEER2 rating most accurately reflects overall system cooling efficiency on a seasonal basis.
 - Energy Efficiency Ratio (EER). EER/EER2 reflects the system's cooling energy efficiency at peak day operations.
- You can switch between cooling and heating directly from the thermostat, putting you in complete control.



Brown County Rural Electrical Association (REA) 24386 State Hwy 4, PO Box 529 Sleepy Eye, MN 56085 800-658-2368 507-794-3331 www.browncountyrea.coop



CAC AND ASHP TUNE UP

- The best way to ensure efficient operation of your cooling system is by having a tune-up every two years.
- A tune-up by a service expert can improve your unit's efficiency by as much as 20% and extends equipment life.
- Equipment must be at least three years old and not received a tune-up rebate in two years to qualify.

DUCTLESS/MINI-SPLIT ASHP

- Use 60% less energy than standard home electric resistance-based heating systems, because they transfer instead of generate heat.
- Use sophisticated compressors and fans that can adjust speeds to save energy. You can cut cooling costs by 30% compared to conventional room air conditioners.
- To qualify for a rebate this equipment must be Energy Star certified.

ELECTRONICALLY COMMUTATED MOTOR (ECM) FOR YOUR FURNACE

- ECMs are standard in new construction. Rebates are available only for replacement.
- ECMs help save energy and money by running at the best speed, opposed to traditional motors that always run at top speed.
- Furnaces equipped with an ECM have lower annual operating costs and can save you \$40 to \$300 per year depending on how you use the furnace fan.

GROUND SOURCE HEAT PUMP

- The most efficient residential heating and cooling system available today.
- Provide energy savings of 20-50%, which results in recouping your investment in only a few years.
- Heating efficiencies 50-70% higher than other heating systems and cooling efficiencies 20-40% higher than available air conditioners.

Choosing higher efficiency heating and cooling equipment can have a big impact on your comfort while helping you save money.

Heating and Cooling



Rebate Application

| MEMBER INFORMATION | | |
|--|---|------------------------------|
| Name | me Account # | |
| Address | | |
| City 5 | State ZIP Phone | |
| Member Type | Renter Landlord Builder es for which I am claiming a rebate are qualifying prod ooperative account. | r |
| Signature | Today's date | |
| EQUIPMENT – TUNE UPS, ECI | MS AND GSHPS, DUCTLESS ASHPS | |
| Cooling Equipment Tune Up | | |
| Equipment Brand | Model Number Serial Serial Serial | Number |
| Approx. age of unit yrs. Size in to | onsHSPF2/SEER2 rating | |
| For Central Air or ASHP Tune Ups: I certify that I have completed the following | on this unit. | |
| | ded 🗌 test all controls & blow out drain lines ed 🗌 check indoor furnace filter & educate hom | neowner on system operation |
| □ check coolant pressure visually & inspec | ct entire system | |
| | AHRI Number | |
| • | ss ASHP qualifying criteria – must be ENERGY ST Model Number | |
| HSPF2/SEER2 rating | | |
| Backup heat source: Electric resistance KW | | |
| Contractor Name | City | State |
| Contractor signature | Contractor company | |
| IMPORTANT: | | |
| Check with cooperative for qualifying Product(s) must be installed within the Include a copy of the original dated sa Submit to: Brown County REA, PO Box 5 | e cooperative's service territory. | p FAX 507-794-4282 |
| • To verify specific model efficiency rati | ngs or ENERGY STAR certification status please vi | isit the following resources |
| Replacement furnaces | ectory.org/Search/SearchHome?ReturnUrl=%2f finder/product/certified-furnaces/results | |
| https://www.ahridirectory.org/Searc | h/SearchHome?ReturnUrl=%2f | * |
| | tar.gov/productfinder/product/certified-geothermal-hea | |
| | ncellation without notice. Call the cooperative to ve -2368 or 507-794-3331 | any repare program status |

Air Source Heat Pumps & Hybrid Systems

Rebate Application

| MEMBER INFORMATION | | | |
|---|--|--|--|
| Name | Account # | | |
| Address | | | |
| City | State ZIP Phone | | |
| Member Type 🛛 Homeowner | Renter Landlord Builder Other | | |
| EQUIPMENT AND INSTALL | ATION INFORMATION | | |
| 0 | 3 SEER2 7.5 HSPF2 🗌 Load-controlled,non-electric back-up 🗌 Not load-controlled SEER2 8.5 HSPF2 🗌 Load-controlled,non-electric back-up 🗌 Not load-controlled | | |
| ASHP alternate/backup heating system typ | pe Electric ResistanceTotal KW Propane/Nat Gas/Fuel Oil | | |
| Manufacturer | Heat pump AHRI number | | |
| | Condenser serial number | | |
| Evaporator coil model number | Evaporator coil serial number | | |
| Furnace model number (if new) | Furnace AHRI number | | |
| Installation date Sta | artup/testing date Outdoor temp* ° F *Follow minimum as set by manufacturer | | |
| EQUIPMENT VERIFICATION | J | | |
| A completed load calculation is on file (initi | ial here) | | |
| • The outdoor unit is matched to the approp | riate indoor coil. AHRI reference number (initial here) | | |
| • Airflow is appropriate for the installation. (Airflow depends on the manufacturer, and should u | (initial here) not be too high or too low — approximately 300 — 400 CFM per ton of cooling capacity. | | |
| Refrigerant charge has been tested and features | ound to be appropriate for the installation. (initial here) | | |
| • Total size of the system in tons. (initial he | ire) | | |
| CONTRACTOR INFORMATIO | ON | | |
| NOTE: An invoice showing the purchase AHRI certificate must be submitted with | e date, equipment manufacturer, model numbers and serial numbers along with the n the application. | | |
| Contractor Company Name | | | |
| Installation Technician | Phone | | |

 HVACR Contractor ID # _____
 OR
 NATE Certification # _____

I hereby certify that all information is accurate, including claims of efficiency, size and member information.

Contractor Signature _____ Date _____

REA

Heating and Cooling

2025 Reference and Conversion Sheet

Notice: On January 1, 2023 the Department of Energy (DoE) began using a new testing procedure to rate the efficiency of air conditioners and air source heat pumps. These changes require new metrics (SEER2/EER2/HSPF2) that were derived from the DoE's new test procedure (M1) rather than the historical metrics (SEER/EER/HSPF) from the old test procedure (M).

The simple conversion table below will help you to identify air conditioning (AC) and air source heat pump (ASHP) equipment that qualifies for ENERGYWISE rebates in 2025 using the following steps.

Step 1: Determine what ratings system was used for the equipment model that you plan to purchase.

Step 2: Confirm that the efficiency ratings of the new equipment exceeds the requirements for the rebate measure you are applying for using the table below to convert between the old and new efficiency ratings when needed.

| SEER | DUCTED SEER2 | DUCTLESS SEER2 |
|------|-----------------|-------------------|
| 14.0 | 13.4 | 14.0 |
| 14.5 | 13.8 | 14.5 |
| 15.0 | 14.3 | 15.0 |
| 15.5 | 14.8 | 15.5 |
| 16.0 | 15.2 | 16.0 |
| 17.0 | 16.2 | 17.0 |
| 17.5 | 16.7 | 17.5 |
| 18.0 | 17.2 | 18.0 |
| 19.0 | 18.1 | 19.0 |
| 20.0 | 19.0 | 20.0 |

| EER | DUCTED EER2 | DUCTLESS EER2 |
|------|----------------|------------------|
| 10.2 | 9.8 | 10.2 |
| 11.0 | 10.5 | 11.0 |
| 11.5 | 11.0 | 11.5 |
| 11.7 | 11.2 | 11.7 |
| 12.0 | 11.5 | 12.0 |
| 12.2 | 11.5 | 12.2 |
| 12.5 | 12.0 | 12.5 |
| 13.0 | 12.5 | 13.0 |

| HSPF | DUCTED SPLIT HSPF2 | DUCTED PACKAGE HSPF2 | DUCTLESS HSPF2 |
|------|-----------------------|-------------------------|-------------------|
| 8.0 | 6.8 | 6.7 | 7.7 |
| 8.2 | 7.0 | 6.9 | 7.9 |
| 8.8 | 7.5 | 7.4 | 8.4 |
| 9.0 | 7.7 | 7.6 | 8.6 |
| 9.5 | 8.1 | 8.0 | 9.1 |
| 10.0 | 8.5 | 8.4 | 9.5 |
| 11.0 | 9.4 | 9.2 | 10.4 |

NOTE: The cross references for efficiency in the above tables should be noted as approximate.

